



HENRED

6/12m TAUTLINER LINK

Zimbabwe's Official Sinotruk and Powerstar Dealer.

24 Martin Drive, Msasa, Harare | trucks@sinopower.co.zw | 0787 319 451



TECHNICAL SPECIFICATIONS		
6.1m & 12.2m TAUTLINER SUPERLINK COMBINATION (STANDARD MEDIUM DUTY)		
Estimated payload	35 ton. Subject to change according to Truck and Trailer Combination Weight.	
Bin length	6100MM Front 12200 Back	
Description	6.1/12.2m link tautliner Trailer	
Standard Specifications		
RUNNING GEAR	Axle	FREUHAUF 11000, 146mm round hollow beam, 90mm diameter journal with interchangeable inner and outer bearings equipped with 420 x 180 'S' cam brakes
	Suspension	Fruehauf "J" suspension, fabricated hangers, 7 blade underslung springs rubber bushed radius rods, hanger brackets welded to frame, 1000mm spring centres
	Tyres:	17 x 315/80R 22.5 tyres Rims: 17 x Steel Wheel Rims 9.00" x 22.5" Spigot
	Brake System:	WABCO HYBRID R6 Brake System, in accordance with SABS, designed to meet higher brake regulations.
	Landing Legs:	FRUEHAUF 'two speed', HEAVY DUTY wind up, rolling foot, one set on front trailer only.
	Lights & Wiring:	DIN 7 pin socket, 24-volt system, dual LED combination stop, tail and separate indicator lights, according to SABS specifications.
BODY STRUCTURE	Chassis:	130 X 12mm and 130 x 12mm BS4360 Grade 55C Steel flange, 4mm supraform T M 42-0 web in neck transition areas in 4mm in main section. Beams are suitably reinforced at joint
	Kingpins:	2" SAE king pin manufactured from 709M40 condition "T" high strength steel and secured with castellated nut. Coupling height unlade of front and rear trailer is 1320mm
	Roof:	Fabricated steel box main member, aluminium to hat roof bows extruded aluminium curtain rails with rubber weather strip and 0.9mm thick one piece composite material. Glass reinforced plastic
	Headboard/ Tailboard	Full height composite GRP/FRP material
	Bumper:	100 x 1.6mm rear under ride bumper, 2400mm wide on front link. 114 x 4.5mm rear under ride bumper, 2400mm wide on rear link.
	Floor:	3mm supra form steel plated welded continuously to peripheral rails and space welded on underside to Crossmember
	Crossmember:	126 x 30 x 4mm M.S one piece cold rolled channels at 500mm pacing
	Spare Wheel Carrier:	2 x Bolt on winch-up type spare wheel carrier, on near side.
	Side Rails:	160 X 50 X 4mm cold rolled HF type channel
	Front & Rear Rails	C-Channel section
EXTRAS	Toolbox:	490L Steel Lockable toolbox.
	Tarpaulin:	Roll Over. 800gsm tarpaulin cover secured with round tube on one side and winding mechanism on the other.
	Mudflaps:	Henred Fruehauf or SA Truck Bodies anti -sail type.
	Paint:	All steel cleaned, primed and finished.

Visit www.sinopower.co.zw for more information on our Henred Trailers

Zimbabwe's Official Sinotruk and Powerstar Dealer.

24 Martin Drive, Msasa, Harare | trucks@sinopower.co.zw | 0787 319 451

 **SINOPOWER**
COMMERCIAL VEHICLES