

Zimbabwe's Official Sinotruk and Powerstar Dealer.



Make	Weichai Euro 3 Turbo Charged			
Model Configuration	WP 12.460N			
Max Power - KW @ R/Min	338/1900			
Max Torque - N.M @R/Min	2110/1000-1400			
НР	460			
Cylinder	6 Inline			
Water Cooled	Yes			
Direct Injection	Yes			
Engine Driven PTO	No			
Displacement (l)	11.596			
Compression Ratio	17:01			
BRAKES				
Service	Dual Circuit Air Brake			
Emergency / Parking	Spring Potential Brake			
Auxiliary	ABS & EVB			
STANDARD TYRE EQUI	PMENT			
Size and ply rating	315/80R22.5 Incl Spare Wheel			
FRONT AXLE				
Туре	VR4/01C-7.5 Disc Brake			
Suspension	3 Leaf spring, hydraulic shock absorbe transverse stabilizer			
MIDDLE & REAR AXLE				
Туре	HD6/27DG-13 & HL6/330D13 HYPOID			
Suspension	DRUM BRAKE, BEIBEN440 Stabilization suspension, 4 leaf spring			
ELECTRICAL EQUIPME	NT			
Alternator	80 AMP			
Starter Motor	5.5Kw			
Detteries	2 x 12V - 165Ah			
Batteries				
PERFORMANCE DATA				
	22% @ GVM			
PERFORMANCE DATA	22% @ GVM 107km/h (Limited to 80km/h)			
PERFORMANCE DATA Gradeability @ GVM				
PERFORMANCE DATA Gradeability @ GVM Max Geared Road Speed	107km/h (Limited to 80km/h)			
PERFORMANCE DATA Gradeability @ GVM Max Geared Road Speed Final Drive Ratio	107km/h (Limited to 80km/h)			

TRANSMISSION								
Make/Mod	Make/Model			Fast Gear 16JZSD240A AMT				
No Gears			16					
Synchromesh or Constant Mesh			Synchromesh					
PTO & Retarder			No. FHB320B					
RATIO								
Crawler		8th	;	3.78	16th	0.83		
1st	14.03	9th	;	3.08	Reverse L	16.3		
2nd	11.64	10th	2	2.56	Reverse H	13.42		
3rd	9.6	11th	2.11					
4th	7.97	12th	1.75					
5th	6.64	13th	1.46					
6th	5.51	14th	1.21					
7th	4.55	15th		1.00				
DIMENSIONS								
Overall Length (OL)			6 905					
Overall Width (OW)			2 500					
Overall Height (OH)			3 475					
Front Overhang (FOH)			1 515					
Rear Overhang (ROH)			703					
Wheel Base (WB)			3 975					
Bumper to Back of Cab (BBC)			2 635					
Cab to rear axle / unit (CA)			2 905					
Turning Radius (TR)			9					
Fuel Tank (Fuel Tank Capacity (FTC)				650 ltr Aluminium			
DIMENSIONS								
Gross Vehicle Mass (GVM)				26 000				
Gross Combination Mass (GSM)				65 000				
Front Axle Mass (GA)				7 500				
Rear Axle Mass (GAU)				26 000				
Permissible	Permissible Maximum Vehicle Mass (V)			25 500				
Permissible	Permissible Maximum Front Axle Mass (AR			7 500				
Permissible	Permissible Maximum Rear Axle Mass (AR)			18 000				
Unladen Front Axle Mass (UF)			5 074					
Unladen Rear Axle Mass (UR)				4 026				
Total Unladen Mass (UT)				9 100				
Permissible Max Drawing Vehicle Mass (D			(D/T)	66 00	0			
САВ								
Day Cab	Day Cab Yes. Hydraulic tiltable cab							

Visit www.sinopower.co.zw for more information on our Power VX Series



New Vehicle

2 Years/ 200,000km