

FT8 4X2

CUMMINS EURO III / 170 HP / 2 Years / Unlimited Mileage Warranty







Zimbabwe's Official Sinotruk and Powerstar Dealer.



ENGINE	
Make	Cummins Euro III
Model Configuration	ISF3.8s3168
Max Power - KW @ R/Min	125/2600
Max Torque - N.M @R/Min	600/1300~1700
НР	170
Cylinder	4 Inline
Water Cooled	Yes
Direct Injection	Yes / Common Rail
Engine Driven PTO	No
Displacement (I)	3.76
Compression Ratio	17.2:1
BRAKES	
Service	Air Brake
Emergency / Parking	Spring Potential Brake
Auxiliary	Exhaust Brake
STANDARD TYRE EQUIPMENT	
Size and ply rating	8.25R20
FRONT AXLE	
Туре	Forged I-beam
Suspension	Non-independent, front & rear leaf spring
Brake	Disc
REAR AXLE	
Туре	Integral
Suspension	Non-independent, front & rear leaf spring
Brake	Drum
ELECTRICAL EQUIPM	IENT
Alternator	70 AMP
Alternator Starter Motor	70 AMP 24 Volt/3.6 KW
Starter Motor	24 Volt/3.6 KW 2 x 12V - 100Ah
Starter Motor Batteries	24 Volt/3.6 KW 2 x 12V - 100Ah
Starter Motor Batteries PERFORMANCE DATA	24 Volt/3.6 KW 2 x 12V - 100Ah
Starter Motor Batteries PERFORMANCE DATA Gradeability @ GVM	24 Volt/3.6 KW 2 x 12V - 100Ah 30%
Starter Motor Batteries PERFORMANCE DATA Gradeability @ GVM Max Geared Road Speed Final Drive Ratio	24 Volt/3.6 KW 2 x 12V - 100Ah 30% 105km/h (Limited to 80km/h)
Starter Motor Batteries PERFORMANCE DATA Gradeability @ GVM Max Geared Road Speed	24 Volt/3.6 KW 2 x 12V - 100Ah 30% 105km/h (Limited to 80km/h)
Starter Motor Batteries PERFORMANCE DATA Gradeability @ GVM Max Geared Road Speed Final Drive Ratio CLUTCH	24 Volt/3.6 KW 2 x 12V - 100Ah 30% 105km/h (Limited to 80km/h) 5.286
Starter Motor Batteries PERFORMANCE DATA Gradeability @ GVM Max Geared Road Speed Final Drive Ratio CLUTCH Make / Type / Size	24 Volt/3.6 KW 2 x 12V - 100Ah 30% 105km/h (Limited to 80km/h) 5.286

TANSMISSION		
Make/Model	ZF Ecolite 6S600	
No Gears	6	
Synchromesh or Constant Mesh	Synchromesh	
Transfer Box	N?A	
РТО	No PTO - PTO Interface only	
RATIO		
1st	6.198	
2nd	3.287	
3rd	2.025	
4th	1.371	
5th	1.00	
6th	0.78	
Reverse Gear Ratio	5.681	
DIMENSIONS		
Overall Length (OL)	8715	
Overall Width (OW)	2 303	
Overall Height (OH)	2510	
Front Overhang (FOH)	1 195	
Rear Overhang (ROH)	2 320	
Wheel Base (WB)	5 200	
Bumper to Back of Cab (BBC)	1 960	
Cab to rear axle / unit (CA)	4 435	
Turning Radius (TR)	9.15	
Fuel Tank Capacity (FTC)	200 ltr Aluminium	
DIMENSIONS		
Gross Vehicle Mass (GVM)	13 095	
Gross Combination Mass (GSM)	21 000	
Front Axle Mass (GA)	4 500	
Rear Axle Mass (GAU)	9 000	
Permissible Maximum Vehicle Mass (V)	13 095	
Permissible Maximum Front Axle Mass (AR) 4 500	
Permissible Maximum Rear Axle Mass (A	NR) 9 000	
Unladen Front Axle Mass (UF)	2 120	
Unladen Rear Axle Mass (UR)	1760	
Total Unladen Mass (UT)	3 880	
Permissible Max Drawing Vehicle Mass	(D/T) 21 000	
CAB		
Day Cab Yes		

Visit www.sinopower.co.zw for more information on our Power FT Series

