



HENRED //

6.1m x 12.2 FLATDECK LINK

Zimbabwe's Official Sinotruk and Powerstar Dealer.

24 Martin Drive, Msasa, Harare | trucks@sinopower.co.zw | 0787 319 451

SP **SINOPOWER**
COMMERCIAL VEHICLES

TECHNICAL SPECIFICATIONS

6.1m x 12.2m FLAT DECK LINK COMBINATION (STANDARD MEDIUM DUTY)

Estimated payload 36ton. Subject to change to Truck and Trailer Combination Weight and Specification

Bin length Front: 6 100mm Back: 12 200mm

Description 6.1m x 12.2m Flat Deck Link Trailer

Standard Specifications

RUNNING GEAR	Axle	FREUHAUF 11000, 127mm round hollow beam, 90mm diameter journal with interchangeable inner and outer bearings equipped with 420 x 180 'S' cam brakes	
	Suspension	FRUEHAUF 'F' suspension, fabricated hangers, 7 blade springs rubber bushed radius rods, hanger brackets welded to frame, 1000mm spring centers.	
	Tyres:	17 x 315/80R 22.5 tyres	Rims: 17 x Steel Wheel Rims 9.00" x 22.5" Spigot
	Brake System:	WABCO HYBRID R6 Brake System, in accordance with SABS, designed to meet higher brake regulations.	
	Landing Legs:	FRUEHAUF 'two speed', HEAVY DUTY wind up, rolling foot, one set on front trailer only.	
	Lights & Wiring:	DIN 7 pin socket, 24-volt system, dual LED combination stop, tail and separate indicator lights, according to SABS specifications.	
BODY STRUCTURE	Chassis:	130 x 8mm Top and 12mm Bottom BS4360 Grade 55C steel flanges, 5mm M.S. web in neck transition areas and 4mm in main section. Beams are suitably reinforced at joints.	
	Kingpins:	2" SAE king pin manufactured from 709M40 condition "T" high strength steel and secured with castellated nut. Coupling height unlade of front and rear trailer is 1320mm	
	Floor:	2.5mm Supraform steel plated welded continuously to peripheral rails and space welded on underside to Crossmembers.	
	Headboard	1 000mm high plated with round bar frame above.	
	Bumper:	100 x 4.5mm and 114 x 4.5mm rear under ride bumper, 2400mm wide.	
	Lashing Hooks:	2 x 12mm diameter hooks at rear. 12mm diameter hooks spaced at 500mm on side rails.	
	Front & Rear Rails:	1750x 50 mm C-pressing.	
	Side Rails:	150 x 54mm RSC	
	Crossmembers:	100 x 30 x 3mm M.S. one piece cold rolled channels at 500mm spacing.	
	Dropsides:	1 200mm 2mm Mild Steel Quick Removable Dropsides	
	Corner Piece Carrier:	1 200mm LH Side	
	Load Lock Winches:	18 winches with 9m, 4ton belts alternately positioned.	
Rubbing Plate:	8mm Supraform plate reinforced with extra deep Crossmembers. Std. 2" SAE pin manufactured from 709M40 condition "T" high strength steel and secured with castellated nut and split pin.		
EXTRAS	Spare Wheel Carrier:	2 x Bolt on winch-up type spare wheel carrier, on near side.	
	Toolbox:	150L Plastic Lockable toolbox.	
	Tarpaulin:	700g Flat Tarpaulins	
	Mudflaps:	Henred Fruehauf or SA Truck Bodies anti -sail type.	
	Paint:	All steel cleaned, primed and finished.	

Visit www.sinopower.co.zw for more information on our Henred Trailers

Zimbabwe's Official Sinotruk and Powerstar Dealer.

24 Martin Drive, Msasa, Harare | trucks@sinopower.co.zw | 0787 319 451

SP SINOPOWER
COMMERCIAL VEHICLES