



**HENRED**

# 45m<sup>3</sup> SIDE TIPPER LINK

Zimbabwe's Official Sinotruk and Powerstar Dealer.

24 Martin Drive, Msasa, Harare | [trucks@sinopower.co.zw](mailto:trucks@sinopower.co.zw) | 0787 319 451

**SP** **SINOPOWER**  
COMMERCIAL VEHICLES

<b>TECHNICAL SPECIFICATIONS</b>		
45m <sup>3</sup> TANDEM SIDE TIPPER INTERLINKS		
<b>Estimated payload</b>	35,5ton. Subject to change according to Truck and Trailer Combination Weight.	
<b>Bin length</b>	7,5m	
<b>Description</b>	45m <sup>3</sup> Tandem interlink side tipping trailer with 3mm Supraform bins.	
<b>Standard Specifications</b>		
<b>RUNNING GEAR</b>	<b>Axle</b>	<b>FREUHAUF</b> 11000, 146mm round hollow beam, 90mm diameter journal with interchangeable inner and outer bearings equipped with 420 x 180 'S' cam brakes
	<b>Suspension</b>	<b>WEWELER 10Ton Air Suspension</b>
	<b>Tyres:</b>	17 x 315/80R 22.5 tyres      Rims: 17 x Steel Wheel Rims 9.00" x 22.5" Spigot
	<b>Brake System:</b>	<b>WABCO HYBRID</b> R6 Brake System, in accordance with SABS, designed to meet higher brake regulations.
	<b>Landing Legs:</b>	<b>FRUEHAUF</b> 'two speed', HEAVY DUTY wind up, rolling foot, one set on front trailer only.
	<b>Lights &amp; Wiring:</b>	DIN 7 pin socket, 24-volt system, dual LED combination stop, tail and separate indicator lights, according to SABS specifications.
<b>BODY STRUCTURE</b>	<b>Chassis:</b>	Fabricated "I" beam with 130 x 8mm Front Trailer & 130 x 12mm Rear Trailer hi- grade 55C steel top and bottom flanges. 4mm Supraform steel web plates suitably reinforced in transitional areas. 8mm Supraform steel rubbing plate.
	<b>Kingpins:</b>	2" SAE king pin manufactured from 709M40 condition "T" high strength steel and secured with castellated nut. Coupling height unlade of front and rear trailer is 1320mm
	<b>Body:</b>	V shaped construction. 3mm Supraform steel floor and side plates. - Bin Painted black on inside.
	<b>Headboard</b>	3mm Supraform Steel plates.
	<b>Bumper:</b>	114 x 100 x 5mm Round rear under ride bumper 2 400mm wide.
	<b>Lashing Hooks:</b>	3 x 10mm diameter hooks at front and rear.
<b>EXTRAS</b>	<b>Spare Wheel Carrier:</b>	2 x Bolt on winch-up type spare wheel carrier, on near side.
	<b>Toolbox:</b>	490L Steel Lockable toolbox.
	<b>Tarpaulin:</b>	Roll Over. 800gsm tarpaulin cover secured with round tube on one side and winding mechanism on the other.
	<b>Mudflaps:</b>	Henred Fruehauf or SA Truck Bodies anti -sail type.
	<b>Paint:</b>	All steel cleaned, primed and finished.

Visit [www.sinopower.co.zw](http://www.sinopower.co.zw) for more information on our Henred Trailers